



PRODUCT ADVANTAGES

- Extra capacity by side wash system: capacity up to 6 GN-trays 1/1 or 4 EN2 container
- Detergent direct spraying system: system soaks the wash ware following the detergent pre-washing cycle and softens even the most severely encrusted food residues
- VISIOTRONIC control: single button control with remaining time indicator together with text and graphic display
- SENSO-ACTIVE resource management: constantly measures the quality of the wash water and keeps the amount of rinsing needed in each rinse cycle to the minimum in order to guarantee a fully hygienic wash result
- POWER wash: high-pressure washing to wash heavily soiled wash items
- CLIP-IN wash and rinse arms: wash and rinse arms can be removed with one hand and without any tools
- USB-interface: comfortable download of operational data in form of a protocol via USB
- GENIUS-X² fine filter system: advanced filter system with pre-wash function reduces detergent consumption up to 35%
- ROTOR-X wash system: separate rotating upper and lower 4-spoke wash arms deliver dynamic wash power
- VAPOSTOP (optional): prevents vapour to escape from machine when door is opened
- The optional drain heat recovery transfers heat from hot drain water to the fresh-water supply, saving up to 7.4 kW
- The optional exhaust heat recovery uses steam to heat fresh feed water and reduces the amount of power needed, saving up to 4.5 kW
- Loading height: above-average loading height of 860 mm
- Intelligent energy management: the available energy is used continuously. Thus, at a low total loading value the heating time gets reduced
- VAPO-ACTIVE steam washing: significantly less manual pre-cleaning and second runs by intensive wash cycles with steam injection
- Interlocked strainer: prevents operation without tank strainer
- EASY-CLEAN concept: blue markings in the machine help the operator to identify the components which require cleaning
- Hygiene programme: for removal of calcium carbonate and other deposits from wash chamber

TECHNICAL DATA


Cycle times*	120 / 240 / 280 sec. and special cycles
Water consumption	8 l/rack
Tank capacity	80 litres
Tank heating	3.3 kW
Power supply	415 / 50 / 3N
Booster loading	
Standard	15.3 kW
Alternative	9.1 kW
Total loading	
Standard	18.5 kW 3 x 32 A
Alternative	15.5 kW 3 x 25 A
Wash pump	2.9 kW 1,150 l/min
Rack size	600 x 760 mm
Loading height	860 mm
Noise level	66 dB (A)
Weight (gross / net)	232 / 212 kg

*Thermostop guarantees required temperatures with cold water connection, the actual cycle times extend accordingly.

CONNECTIONS

① Drain hose	1,800 mm ID20 / OD25
② Supply hose	2,000 mm R 3/4"
Required flow rate	5 l/min
Flow pressure	0.5 – 6 bar
Max. supply water temperature	60 ° C
③ Power cord	2,000 mm
Supply hose for	
④ Detergent	2,500 mm
⑤ Rinse aid	2,500 mm

DIMENSIONAL DRAWING



- * Loading height can be reduced to 650mm
- ** Height can be reduced to 2,200mm with the door open
- *** With exhaust heat recovery
- **** With heat recovery
- **** Distance between lateral guide rails: 520mm

