



Benches etc not included

PRODUCT ADVANTAGES

- **Easy-to-use** electronic controls with 2 cycles - 60 & 90 seconds
- Electronic temperature gauges
- Suitable for all dish & glass washing applications. **Useable chamber height of 440mm**. Able to wash 1/1 GN pans when using optional open ended tray racks
- **Low 2.8 litres per cycle rinse volume** dish / glasswasher with **Rinse Pump** to guarantee rinse volume and pressure
- **Fully enclosed 4 sided hood design** - avoiding loss of energy / steam
- Optimum hygienic - deep drawn tank with coved corners (no welds) and **SELF-CLEANING CYCLE**
- Stainless steel wash and rinse arm with **patented WIDE ANGLE FAN** nozzle to maximise wash & rinse performance
- Wash pump inlet strainer to ensure machine reliability
- Includes chemical dispensers, fill hose, power lead & pump-out drain for quick & easy installation
- Includes 1 x plate rack & 1 x cutlery holder
- Back flow prevention device as standard to meet Watermark Approval & ATS 5200.101
- **MADE IN GERMANY**

Technical Data

Drain connection	Pump-out drain standard - 20mm inner / 25mm outer
Fresh water connection: pressure hose 1000mm flow pressure	Connection size: 3/4" BSP 50-1000kPa
Incoming water temperature	55-65°C
Power cord	3 phase lead
hose for detergent hose for rinse aid	2000mm each
wash tank temperature	55-65°C
Rinse water temperature (booster tank)	Minimum 82°C
Low temp cut-out (thermostop) activated	Yes
cycle times	60 sec. 90 sec.
water consumption	2.8litres
tank capacity	21 litres
tank heating	2.5kW
power supply	425/50/3
booster loading	6.2kW
total loading	7.1kW
pump capacity	0.7kW
loading height	440mm
bench to bench - internal dimension	628mm

* Thermostop guarantees required rinse temperatures. The actual cycle time extends accordingly if the machine is connected to cold water or run on single phase

* For machine protection water hardness should not exceed 3°dH. If higher we recommend using a water softener - ask your Hobart representative for assistance.

DIMENSIONAL DRAWING

