

ECOMAX PLUS F515 DISHWASHER



Due to the high wash power, the double-walled housing and the robust filter systems, it is the quiet and resource-saving solution for your busy workday life.

Dishwasher ecomax plus F515

Cycle times*	60/120/180 sec.
Capacity per hour*	up to 60 racks
Wash/rinse temperature	approx 60° C / approx 82°C
Tank capacity	10.6
Fresh water consumption/rack	2.3
Wash pump	0.6 kW
Heating booster/tank	2.1 kW
Total loading	2.9 kW 15A
Rated voltage	240/50/1
Width/Depth/Height	600/600/825 mm
Loading height	425 mm
Rack size	500 x 500 mm

^{*}hot water connection

PRODUCT ADVANTAGES

- Electronic control with digital temperature indication
- Flat surface of control panel
- 3 selectable wash cycles
- Rotating top and bottom wash system to distribute the wash water evenly over the dishes
- · Indented nozzles prevent blocking
- Thermostop-function for guaranteed rinse temperatures
- Integrated self-cleaning cycle
- Stainless steel rinse arm and housing
- Removal of rinse arms without any tools
- · Easy access to all parts
- Deep-drawn wash tank
- Double-walled housing and heat insulated front door
- Tank strainer, coarse filter and pump suction casing
- · Door damping control
- Loading height above average: 425 mm, for easy loading of large plates
- Fully equipped with detergent and rinse aid dispenser, rinse pressure pump and drain pump



STANDARD EQUIPMENT

- Watermark Approved
- Plate rack P-18-12
- Universal flat rack B-00-07
- Plastic cutlery rack with 4 boxes 01-246175-1
- Rinse aid & detergent dispensers
- Electric cable, flexible water supply hose and drain hose
- Rear panelling

