

## **ECOMAX G404**GLASSWASHER



The fast and reliable glasswasher in compact design. Perfect for start-ups, small bars or restaurants.

## Glasswasher ecomax G404

Cycle times*	60 / 120 sec.
Capacity per hour*	up to 60 racks
Wash/rinse temperature	approx 55° C / approx 60° C
Tank capacity	10 I
Fresh water consumption/rack	2.0
Wash pump	0.18 kW
Heating booster/tank	1.9 kW
Total loading	2.1 kW
Rated voltage	240/50/1- 15A
Width/Depth/Height	436/534/700mm
Loading height	308 mm
Rack size	17x14" (431 x 355mm)


\*hot water connection\*
Machine supplied with 150mm adjustable legs


## **PRODUCT ADVANTAGES**

- Electronic control with digital temperature indication
- Flat surface of control panel
- 2 selectable wash cycles
- Rotating top and bottom wash system to distribute the wash water evenly over the dishes
- Indented nozzles prevent blocking
- Thermostop-function for guaranteed temperatures
- Integrated self-cleaning cycle
- Removal of rinse arms without any tools
- USB connection for easier service access
- Easy access to all parts
- Deep drawn rack track
- Door safety lock
- Double-walled insulated front door
- Integrated cycle counting, e.g. for control of water treatment system

## STANDARD EQUIPMENT

- Glass rack 17x14"
- Rinse aid & detergent dispensers
- Electric cable, flexible water supply hose and drain hose
- Rear panelling





① Drain hose	2,000 mm
	ID20/OD25
② Supply hose	2,000 mm   R 3/4"
Required flow rate	5 l/min
Flow pressure	3.0 -6 bar (300-
	600 kPa)
Max. supply water	60 °C
temperature	
③ Power cord	2,000 mm
Supply hose for	
4 Detergent	2,500 mm
⑤ Rinse aid	2,500 mm