

ECOMAX PLUS G415 GLASSWASHER



The compact glasswasher for hotels, bars and restaurants, that are washing more than a hundred glasses a day.

Glasswasher ecomax plus G415

Cycle times*	60/90/180 sec.
Capacity per hour*	up to 60 racks (900 glasses)
Wash/rinse temperature	60°
Tank capacity	81
Fresh water consumption/rack	2.0
Wash pump	0.6 kW
Heating booster/tank	0.8 kW
Total loading	2.8 kW 15A
Rated voltage	240 / 50 / 1 - 15A
Width/Depth/Height	460/590/700mm
Loading height	315 mm
Rack size	396mmx396mm / 431mmx355mm

*hot water connection *
Machine supplied with 150mm adjustable legs
Line pressure required: 0.8 to 6 bar


PRODUCT ADVANTAGES

- Electronic control with digital temperature indication
- Flat surface of control panel
- 3 selectable wash cycles
- Rotating top and bottom wash system to distribute the wash water evenly over the dishes
- Indented nozzles prevent blocking
- Thermostop-function for guaranteed rinse temperatures
- Integrated self-cleaning cycle
- Stainless steel rinse arm and housing
- Removal of rinse arms without any tools
- · Easy access to all parts
- Deep-drawn wash tank
- Double-walled housing and heat insulated front door
- Tank strainer, coarse filter and pump suction casing
- Door damping control
- Loading height above average: 315 mm, for easy loading of extra high glasses
- Fully equipped with detergent and rinse aid dispenser, rinse pressure pump and drain pump



STANDARD EQUIPMENT

- Watermark Approved
- Glass rack with 4 sloped rows 371450-84
- Rinse aid & detergent dispensers
- Electric cable, flexible water supply hose and drain hose
- Rear panelling



CONNECTIONS	
① Drain hose	2,000 mm ID20/OD25
Reverse Osmosis unit (RO-S)	Independent gravity waste to tundish
② Supply hose	2,000 mm R 3/4"
Flow pressure	0.5 (0.8 with softener)- 6 bar
Max. supply water	60°C
temperature	35°C with RO
3 Power cord	2,000 mm
Supply hose for	
④ Detergent	2,500 mm
⑤ Rinse aid	2,500 mm